

MSDS

Material Safety Data Sheet

02/24/2009

Premier Hot Melt Glue Sticks

I. PRODUCT IDENTIFICATION

Name: Hot Melt Glue Sticks
Class: Thermoplastic Glue Sticks
Emergency Telephone CHEMTREC:
800-424-9300

II. HMIS (0 = minimal hazard; 4 = severe)

Health = 0 Flammability = 1 Reactivity = 0

III. HAZARDOUS INGREDIENTS

None per OSHA Regulation:
29CFR1910.1200 None per SARA Title III,
Section 313 and TSCA 40 CRF 372

IV. PHYSICAL DATA

MELTING POINT: 230°F; BOILING POINT:
Not established; ODOR: Neutral; SPECIFIC
GRAVITY: 0.98; VAPOR PRESSURE: Not
established; VAPOR DENSITY: Not
established

V. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NA; AUTOIGNITION TEM-
PERATURE: Not established; LOWER
EXPLOSIVE LIMIT: Not established;
UPPER EXPLOSIVE LIMIT: Not estab-
lished; EXTINGUISHING MEDIA: A solid
stream of water may scatter molten prod-
uct. UNUSUAL FIRE AND EXPLOSION
HAZARDS: Material will burn in a fire.
SPECIAL FIRE FIGHTING PROCEDURES:
Persons exposed to products of combus-
tion should wear self-contained breathing
apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:
Carbon dioxide, Carbon monoxide

VI. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation,
Ingestion, skin and eye contact. EFFECTS
OF OVEREXPOSURE: Eyes - No irritation
hazard in normal industrial use. Exposure
to hot material may cause thermal burns.
Skin - Skin contact at room temperature is
not irritating. Contact with product at
elevated temperatures can result in
thermal burns. Inhalation - No irritation
hazard in normal industrial use. Ingestion
- Ingestion is not an anticipated route of
exposure.

VII. FIRST AID MEASURES

EYE CONTACT: Use an eye wash to
remove a chemical from your eye regard-
less of the level of hazard. Flush eye with
water for 15 minutes. Get medical atten-
tion. SKIN CONTACT: Wash affected
area(s) thoroughly with soap and water.
For hot material, immediately immerse in
or flush the affected are with large
amounts of cold water to dissipate heat.
cover with clean gauze and do not attempt
to remove the material yourself. Seek
medical attention. Medical personnel: coat
with mineral oil to soften material for
removal. INHALATION: This material does
not present a hazard if inhaled. Remove to
fresh air if necessary. INGESTION: No
hazard in normal industrial use. Do not
induce vomiting. Seek medical attention if
symptoms develop.

VIII. SPILL OR LEAK PROCEDURES

SPECIAL PROTECTION: No adverse health
effects expected from the clean-up of
spilled material. CLEAN-UP: Allow molten
material to solidify before disposal.


IX. PROTECTIVE EQUIPMENT

No safety equipment required other than
goggles.

X. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

Premier believes that data set forth herein
is accurate as of the date hereof, and
makes no warranty with respect thereto
and expressly disclaims all liability for
reliance thereon. Such data are offered
solely for your consideration, investigation
and verification.



PREMIER FLOORING PRODUCTS

www.premiertapeproducts.com
premier@premierapeproducts.com

TRAXX
CORPORATION

1201 E. Lexington Ave • Pomona, CA 91766 • phone: 909-623-8032 • fax: 909-623-8074